



Applicability: KAWASAKI – YAMAHA

Cod. KRBEA-021 – INSTALLATION AND USE



1. Turn off the engine.



2. Locate and disconnect the 4 pin black connector of the o2 sensor.
Follow the silicone sheath coming from the o2 sensor to find the connector.



3. Connect the Rapid Bike connectors in-line with the stock ones.

4. Connect the 6 pin connector and the 2 pin connector to the RapidBike Easy module.



Settings

GREEN LED / LED VERDE



TRIMMER N°1

TRIMMER N°2

The green led shows the state of the device:

Led off = not powered.

Led on = powered, o2 sensor cold.

Led flashing = powered, o2 sensor hot, the device is working.

5. Set the trimmers as follows:

Trimmer 1 = SETTING

Trimmer 2 = FUEL RATIO

MAKE	MODEL	TRIMMER 1	TRIMMER 2
Kawasaki	Ninja 250 R	5	+2
Kawasaki	Other models	6 for stock exhaust 5 for aftermarket exhaust	+2
Yamaha	All models	6 for stock exhaust 5 for aftermarket exhaust	+2 +3

6. Turn on the ignition and verify that the green led is on.
7. Turn on the engine and wait some minutes until the green led starts to flash.
8. Fasten the cover with the screws.

Dimsport Srl

Zona Industriale Madonnina - Loc. San Iorio

15020 SERRALUNGA DI CREA (AL) - ITALY

T (+39) 0142.9552 F (+39) 0142.940094

www.dimsport.it

RapidBike

ASSISTENZA TECNICA – TECHNICAL SUPPORT

Tel. (+39) 0142.9552

E-mail: support.rapidbike@dimsport.it

UFFICIO COMMERCIALE – COMMERCIAL DEPT.

Tel. (+39) 0142.9552

E-mail: info.rapidbike@dimsport.it



a company of
una azienda del gruppo



www.rapidbike.it
